

# QMFZ2.E100553 - Plastics - Component

## Plastics - Component

**ASTAR S A**

Barrio Sangroniz 30  
Sondika, 48150 Spain

E100553

Dsg	Color	Min Thk mm	Flame Class	H		Elec Str	RTI Imp	Mech Str	H	D	C
				V	4				T	9	
Unsaturated Polyester (UP), Bulk Molding Compound (BMC)											
PX177	ALL	1.50 - 1.65	V-0, 5VA	0	0	105	130	130	-	-	0
PX3	NC, BK	1.5	HB	-	-	105	130	130	-	4	-
		3.0	HB	-	-	105	130	130	-	-	-
PX4	ALL	3.0	V-0	0	0	130	130	130	4	4	0
Unsaturated Polyester (UP), Sheet Molding Compound (SMC)											
APG 10R(f2)	NC, GY	1.5	HB	-	-	105	130	130	0	4	0
	BK, GY	3.4	V-0	0	0	105	130	130	-	-	-
		6.0	V-0	0	0	105	130	130	-	-	-
H154 (f1)	ALL	3.0	V-0	0	0	105	130	130	-	-	0
H156(f1)	ALL	2.0	V-0	0	-	105	130	130	-	-	0
		3.0	V-0, 5VA	0	-	105	130	130	-	-	-
H161	ALL	1.5	HB	-	-	105	130	130	-	-	-
		2.5	HB	-	-	105	130	130	-	-	-
		3.0	HB	-	-	105	130	130	-	-	-
H161(f1)	ALL	2.5	HB	-	-	105	130	130	-	-	-

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

Marking: Company name, material designation On container, wrapper Or finished part.

Last Updated on 2022-03-02

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.